


ENGINEERING SPECIFICATION

Zurn Z415-BZ1 floor and shower drain features Dura-coated cast iron body with bottom outlet, combination invertible membrane clamp and adjustable collar with seepage slots, and top assembly. EZ1 drainage series is engineered to simplify product installation, comprised of concrete shield, up to 1" [25] of vertical post pour adjustment, pre-packaged shims for tilt correction and integrated self-contained "Type B" light duty strainer with rough-in cover for protection during concrete pour.

NOTES

Minimum K dimension only with -LR option for $6^{\prime\prime}$ and $8^{\prime\prime}$



	Dimensions in inches							Strainer		
Strainer Designation	A Pipe Size	B Strainer Dia.	D		к		К′		Open Area	
			Min.	Max.	Min.	Max.	Min.	Max.	Sq. In [cm²]	Approximate Weight lb [kg]
-5B	2-3 [51-76]	5 [127]	0	1[25]	1-25/32 [45]	2-31/32 [75]	2-9/32 [58]	3-15/32 [88]	6-1/4 [40]	16 [7]
-6B	2-3-4 [51-76-102]	6 [152]	0	1[25]	1-13/16 [46]	3 [76]	2-5/16 [59]	3-1/2 [89]	9 [58]	19 [9]
-8B	3-4 [76-102]	8 [203]	0	31/32 [25]	2-5/32 [55]	3-11/32 [85]	2-21/32 [67]	3-27/32 [98]	20 [129]	24 [11]
-8B	6 [152]	8 [203]	0	31/32 [25]	2-5/32 [55]	3-11/32 [85]	2-21/32 [67]	3-27/32 [98]	20 [129]	26 [12]

PREFIXES	DESCRIPTION	STRAINER DESIG.	PIPE SIZE	LIST PRICE
ZN415-BZ1*	 D.C.C.I. Body Assembly with Polished Nickel Bronze Top 	-5B	2", 3"	484.00
		-6B	2", 3", 4"	592.00
		-8B	3", 4"	851.00
			6″	1,396.00
ZB415-BZ1	D.C.C.I. Body Assembly with Polished Bronze Top	-5B	2", 3"	460.00
		-6B	2", 3", 4"	535.00
		-8B	3", 4"	807.00
			6″	1,351.00
ZS415-BZ1	D.C.C.I. Body Assembly with Stainless Steel Top	-5B	2", 3"	1,042.00
		-6B	2", 3", 4"	1,298.00
		-8B	3", 4"	1,754.00
			6″	2,299.00
OUTLETS (SPE	CIFY PIPE SIZE IN INCHES AND T	YPE OF OUTLET)		
		PIPE SIZE/	E BODY HT.	חתא

OUTLET	ТҮРЕ	PIPE SIZE/ OUTLET TYPE	E BODY HT. Dim.	ADD
IC	Inside Caulk	2IC, 3IC, 4IC	4-3/16″	N/C
IP	Threaded	2IP	2-7/16″	80.00
		3IP	2-3/4"	80.00
		4IP	2-13/16"	80.00
		6IP	2-7/8″	80.00
NH	No-Hub	2NH, 3NH, 4NH	3-13/16″	N/C
NL	Neo-Loc	2NL, 3NL, 4NL	3-7/8″	N/C

SUFFIXES			ADD
-AR	Acid Resisting Epoxy Coated Cast Iron		171.00
9 -EF	3/4" Extension Frame		299.00
-G	Galvanized Cast Iron		198.00
-LR	Low Rough-In (For 6" & 8" Only)		N/C
-P	Trap Primer Connection (Specify 1/2"*)		N/C
9 -SA	Stabilizer Assembly (See Z1035)		138.00
🤊 – SQ	Stabilizer Q-deck (See Z1035-Q)		184.00
∋ −SR	Stabilizer Ring (See Z400-SR)		121.00
D -TC	Neo-Loc Test Cap Gasket (2", 3", 4" NL Bottom Outlet Only)		24.00
-TSP	Trap Seal Protection Device (Size Matches Drain Outlet Selected, See	Z1072)	POA
-U	2"-3-1/4" High Extension Adapter	D.C.	140.00
		Galv.	306.00
-UP	1-3/4" Pre-Pour Adjustment Extension A	140.00	
-VP	Vandal-Proof Secured Top		58.00
-Y	Sediment Bucket		109.00
BEST SELLE	RS		LIST PRICE
ZN415-2N	ZN415-2NH-BZ1		
ZN415-3N	H-BZ1		484.00
ZN415-3N	H-6BZ1		592.00



877-903-7246 www.commercialplumbingsupply.com

*Regularly furnished unless otherwise specified.

Items designated as Best Sellers are most specified and are generally in stock for shipment. ① This symbol denotes a product that is engineered to reduce installation and rework time. For additional product information, please visit www.zurn.com

TECH INFO

ROOF DRAINS

FLOOR DRAINS

T, P, BW VALVES

INTERCEPTORS

CARRIERS

HYDRANTS

CLEANOUTS

WHA

SS DRAINS

FAB SS DRAINS